
Name

rivendell — Common command-line switches for Rivendell modules

Description

Rivendell is a complete radio broadcast automation system, with facilities for the acquisition, management, scheduling and playout of audio content. This man page covers the set of command-line options supported by all Rivendell modules.

For a comprehensive overview of Rivendell and its features, see the Rivendell Operations Guide [<https://opsguide.rivendellaudio.org/html>].

Basic Options

The following command-line options work with nearly all Rivendell modules:

--help	Print a list of available command-line options and then exit.
--list-styles	Print the list of available Qt style plug-ins to standard output and then exit.
--skip-db-check	Bypass the usual check to ensure that the Rivendell database is using the expected schema version. Useless except for debugging.

Warning

This option is *dangerous*, and can cause *database corruption*! It should only be used as a debugging aid and when you know exactly what you are doing.

--skip-db-check	Bypass the usual check to ensure that the "rivendell" service is running. Useless except for debugging.
-style <i>plugin-name</i>	Use the Qt style plug-in <i>plugin-name</i> .
--ticket=<i>tkl-str</i>	Manually add the ticket string <i>tkl-str</i> to the WebAPI ticket store. Useless except for debugging.
--version	Print the Rivendell version and then exit.

Bugs

The **-style** option uses the X11-style format (single leading hyphen, with a space separating the switch and its value) rather than the Rivendell-style one (double leading hyphens with an equal sign separating the switch and its value).

See Also

rdadmin(1), rdairplay(1), rdalsaconfig(8), rdclilogedit(1), rd.conf(5), rdconvert(1), rddbmgr(8), rdexport(1), rdimport(1), rdlogmanager(1), rdmarkerset(8), rdmetadata(1), rdrender(1), rdservice(8), rdsinglestart(1), rdsoftkeys(1), rmlsend(1)