
Name

rdservice — Rivendell service manager

Synopsis

rdservice [*OPTIONS*]

Description

rdservice(8) manages the various background service components of the Rivendell Radio Automation System, including **caed**(8), **rdcatchd**(8), **ripd**(8), **rdpadd**(8), **rdpadengined**(8), **rdvairplayd**(8), **rdimport**(1) (in dropbox mode) as well as periodic system maintenance tasks using **rdmaint**(8). It is normally invoked by the host's boot system (such as **systemd**(1)) at system boot-time and runs continuously thereafter. There should only be one instance of **rdservice**(8) running at any given time; attempts to start an additional instance will terminate with exit code 1.

Options

<code>--end-startup-after-caed</code> , <code>--end-startup-after-ripd</code> , <code>--end-startup-after-rdcatchd</code> , <code>--end-startup-after-rdpadd</code> , <code>--end-startup-after-rdpadengined</code> , <code>--end-startup-after-rdvairplayd</code> , <code>--end-startup-after-rdrepld</code>	Skip the remainder of the startup sequence after the specified component is started. (Useless except for debugging).
<code>--force-service-maintenance</code>	Force the initial maintenance run to include System maintenance, even if the scheduling algorithm doesn't call for it. (Useless except for debugging).
<code>--initial-maintenance-interval=<i>interval</i></code>	Schedule the initial maintenance run to be started <i>interval</i> milliseconds after startup. (Useless except for debugging).

Exit Values

: 0
: Normal exit
: 1
: Prior instance already running
: 2
: Unable to open database
: 3
: Unable to start a service component
: 4
: Unknown/invalid command line option

See Also

rddbmgr(8), **rdimport**(1), **systemd**(1), **systemctl**(1)